



Specifications Noxion LED Floodlight  
ProBeam V2.0 133-210W  
17300-29400lm 60D - 830-840-865 CCT  
| IP66 - Asymmetrical Type II

[View Product](#)

## General Information

|                          |                                                                                                   |
|--------------------------|---------------------------------------------------------------------------------------------------|
| SKU                      | 248957                                                                                            |
| EAN                      | 8719157049030                                                                                     |
| Manufacturer Code        | 8719157049030                                                                                     |
| Brand                    | Noxion                                                                                            |
| Manufacturer Name        | Noxion LED Floodlight ProBeam V2.0 130/170/210W MAX 29400lm 3CCT Asymmetrical (with Zhaga socket) |
| Any Lamp all-in warranty | 6 Years                                                                                           |
| Average Lifetime (h)     | 150000                                                                                            |

## Technical Information

|                             |                                                 |
|-----------------------------|-------------------------------------------------|
| Technology                  | LED Integrated                                  |
| Wattage                     | 210W                                            |
| Replaces (Watt)             | 600                                             |
| Voltage (V)                 | 220-240                                         |
| Dimmable                    | Not Dimmable                                    |
| Colour Code                 | 830 Warm White, 840 Cool White, 865 Daylight    |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White, 6500 Daylight |
| Colour Rendering (Ra)       | 80-89                                           |
| Colour of Light             | White                                           |
| Light colour options        | CCT                                             |
| Luminous Flux (Lumen)       | 29400lm                                         |

|                          |                |
|--------------------------|----------------|
| Luminous Efficacy (lm/W) | 140            |
| Beam Angle (degree)      | 60             |
| Tiltable                 | Yes            |
| Power factor             | >0.90          |
| Product Type Category    | LED Floodlight |

## Fixture Information

|                        |                 |
|------------------------|-----------------|
| Mounting Method        | Surface         |
| Fixture Connection     | Cable 100cm     |
| Optical Cover          | Glass           |
| Light Distribution     | Asymmetrical    |
| IP-rating              | IP66            |
| Impact Protection (IK) | IK08 - 5 joules |
| Operating Temperature  | 0 to +75        |
| Colour of the Fixture  | Black           |
| Housing                | Aluminium       |
| Series                 | ProBeam         |

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 412 |
| Width (mm)  | 54  |
| Height (mm) | 360 |

## Why Any-lamp?

## Sensor Information

 Type of sensor

Order from the **largest lighting specialist** in Europe

No Sensor

 **Customised** quotation



Up to **7 years warranty**



**Easy** return process